

B28 PURETIC POWERBLOCK

<image>

28J Powerblock

Hydraulic Motors:

B28 Powerblocks are available with 7 sizes of motors including three sizes of 2 speed motors. Haul with high torque or dry up the net at high speed.

Choose a single speed or 2 speed motor. We can size the motor to your hydraulic system based on your requirements for speed or pull. All hydraulic motors are now marinized for longer service life.

Exceeding recommended hydraulic flow requirements of hydraulic motor can result in failure of shaft seal and internal damage

to the hydraulic motor resulting in premature failure of motor. Maximum recommended hydraulic flow is 45 GPM @ 2000 PSI.

Powergrip:

The yoke mounted Powergrip helps keep the net square when hauling, increasing traction and control of the net in rough weather.

Powergrip motors and hydraulic cylinders are marinized for longer service life. Our Powergrip tire assemblies have galvanized rims with new style aluminum covers for long service life in a saltwater environment and are available in a number of different styles, heights and widths to customize the grip based on your net size and fishery.

Hydraulic Swivel:

Rotate your powerblock 360 degrees. The load bearing hydraulic swivel option allows the powerblock to easily haul port or starboard without binding the hydraulic hoses.





Bolt in Cleated Sheave:

4 different styles of cleats are available to customize your powerblock. Rubber, Aluminum, Low Profile Polyurethane, or High Profile Polyurethane.



| Model | Weight LBS | Height Inches |
|----------------------------------|------------|---------------|
| B28J Plain | 430 | 40 |
| B28J With Powergrip | 620 | 50 |
| B28J With Powergrip and Swivel | 710 | 69 |
| B28J-2 With Powergrip and Swivel | 712 | 69 |





| Model | Sheave Speed | | Net Pull | Hydraulic Oil Input * | |
|-----------------------------|--------------|-----------|---------------|-----------------------|--------------|
| | FPM | RPM | @ 1/2 Radius | Flow GPM | Pressure PSI |
| B28J - 015 - B9928J-SWL | 173 | 35 | 4650 | 20 | 2000 |
| B28J - 019 - B9928J-SWL | 172 | 35 | 5870 | 25 | 2000 |
| B28J - 024 - B9928J-SWL | 176 | 35 | 6975 | 32 | 2000 |
| B28J - 030 - B9928J-SWL | 174 | 35 | 8815 | 40 | 2000 |
| B28J - 013/020 - B9928J-SWL | 271H / 176L | 54H / 35L | 4270H / 6100L | 27 | 2000 |
| B28J - 016/024 - B9928J-SWL | 236H / 176L | 53H / 35L | 4650H / 6975L | 32 | 2000 |
| B28J - 020/030 - B9928J-SWL | 261H / 174L | 53H / 35L | 6100H / 8815L | 40 | 2000 |
| | | | | | |

*Maximum recommended continuous hydraulic flow is 45GPM @ 2000 PSI

Sheave capacity is 35 inches of compact net circumference

Smith Berger Marine, Inc.

7915 10th Ave. S., Seattle, WA 98108 USA Tel. 206.764.4650 - Toll Free 888.726.1688 - Fax 206.764.4653 E-mail: sales@smithberger.com - Web: www.smithberger.com